

## UNIQUE SOLUTIONS MADE BY THE SPECIALIST



**Joh. Heinr. Bornemann GmbH**

Industriestraße 2  
31683 Obernkirchen  
Germany

Fon: +49 5724 390-0  
Fax: +49 5724 390-290  
info@bornemann.com  
www.bornemann.com



Germany – Headquarter

### CANADA

**Bornemann Inc.**

320 441, 5th Avenue S.W.  
Calgary, Alberta  
Canada T2P 2V1  
CANADA

Fon: +1 403 294 0777  
Fax: +1 403 262 4073  
info.ca@bornemann.com  
www.bornemann-ca.com

### USA

**Bornemann Pumps, Inc.**

10375 Richmond Ave,  
Suite 1575  
Houston, Texas 77042  
USA

Fon: +1 832 320 25 00  
info.usa@bornemann.com  
www.bornemann-usa.com

Parts and new pump stocking  
**Bornemann Inc.**

P.O. Box 1769  
Matthews, NC 28106  
USA

Fon: +1 704 849 86 36  
Fax: +1 704 849 86 37  
info.usa@bornemann.com  
www.bornemann-usa.com

### ARGENTINA

**Bombas Bornemann S.R.L.**

Armenia 2898  
B1605CDP Munro  
Prov. Buenos Aires  
ARGENTINA

Fon: +54 11 475 680 08  
Fax: +54 11 475 655 41  
info.ar@bornemann.com  
www.bornemann-ar.com

### MEXICO

**Bornemann S.A. de C.V.**

Castillo de Cantburry 16  
52938 Atizapan, Estado de Mexico  
MEXICO

Fon: +52 55 5808 0875  
Fax: +52 55 5808 1108  
info.mx@bornemann.com  
www.bornemann-mx.com

### SINGAPORE

**Bornemann Pumps Asia Pte. Ltd.**

25 Intern. Business Park  
German Centre, # 04-11/12  
Singapore 609916  
SINGAPORE

Fon: +65 656 167 82/3  
Fon: +65 656 159 78  
Fax: +65 656 167 84  
info.sg@bornemann.com  
www.bornemann-sg.com

### CHINA

**Bornemann Pumps & Systems  
(Tianjin) Co., Ltd.**

Jinbin General Building No. 6,  
No. 45 Muning Road  
TEDA, Tianjin  
P. R. China 300457  
CHINA

Fon: +86 22 662 978 00  
Fax: +86 22 253 267 99  
info.service@bornemann-cn.com  
www.bornemann-cn.com


**Bornemann Pumps International  
Tianjin**

Room 1101  
Tianjin Binjiang International Hotel  
No. 105 Jianshe Road  
Heping District, Tianjin  
CHINA

Fon: +86 22 5881 2997  
Fax: +86 22 5881 2996  
info.sales@bornemann-cn.com  
www.bornemann-cn.com

# BORNEMANN PUMPS FOR FOOD, PHARMACEUTICALS AND MORE

## THE STANDARD IN SANITARY PUMPS





# MODULAR SYSTEM




Bornemann SLH twin screw pumps are single-flow and self-priming. Two contact-free intermeshing screws and the pump housing form closed chambers that, according to the direction of rotation, constantly move towards the pressure discharge end of the pump. This axial system enables cautious, low-pulsation conveyance. It protects the media and maintains size, surface and visual integrity of the products.

The 2-in-1 principle conveys and cleans in one pump. Due to the wide range of pump speeds – up to a maximum of 3,600 rpm, process cycles as well as CIP and SIP procedures are possible with just one pump.

The advantages are obvious: no need for a CIP pump or the associated piping, valve and MSR technology. It saves valuable space and reduces your investment costs. The conveyed material passes through the entire pump which enables excellent cleaning and hygienic results. The Bornemann SLH pump is EHEDG and 3A certified.

## 2-in-1 CONVEY AND CLEAN WITH ONE PUMP



SLH 180

- Self-priming down to a vacuum of less than -0.8 bar when the pump is filled
- Can be adapted for nearly any medium
- Large range of speeds, from below 100 up to 3,600 rpm, make it possible to convey with one pump and also use it as a conveying aggregate
- Low-pulsation conveyance
- Excellent cleaning and hygienic properties
- Abrasion-free
- Dry running protection
- Designed for reverse flow capabilities


## IMPRESSIVE SPECTRUM OF PERFORMANCE FEATURES



Receipt of goods with mobile pump




Dairy products conveyance



Melted cheese conveyance



Dairy products conveyance



Model SLH pump



Conveyance of high viscous products



# THE SUM OF MANY ADVANTAGES

## SIX REASONS TO BELIEVE

Bornemann SLH pumps provide you with a range of convincing advantages that together result in the highest possible cost and production efficiency.

Using a modular system, Bornemann offers four pump sizes and different screw sets that cover a conveyance range of 40 l/h to 180 m³/h with a unit size up to 40 mm diameter. The different screw sizes make it possible to handle a wide range of flow capacities with the same viscosities, operating pressures and rotation speeds.

Quick and easy change of the media.

**1** CIP and SIP – easy cleaning and sterilization

**2** High suction performance for more production efficiency

**3** Smooth and pulsation-free handling for sensitive products

**4** Top resistance to wear leads to safe production and long lifetime

**5** Handles the widest range of viscosities

**6** Adaptable to the medium – flexible implementation

# TECHNICAL DATA

## PERFORMANCE DATA

SLH 50 | SLH 80 | SLH 125 | SLH 180

**Output Capacities:**  
up to 40 l/h – 180 m³/h (792 gpm)

**Differential Pressures:**  
up to 16 bar (232 psi)

**Pump Speed:** max. 3,600 rpm

**Viscosity:** max. 500,000 cSt





**Direction of Operation:**  
reversible operation

**Flange Connections:**  
dairy connection according to DIN 11851, aseptic connection according to DIN 11864, other connections varieties upon request

**Heating Medium:** various

**Product Temperature:**  
max. 130°C (266°F)

**Cleaning Temperature:**  
up to 140°C (284°F)



## CONVINCING PERFORMANCE




SLH 125



Low abrasion conveyance of toothpaste



Sausage meat conveyance



Cheese conveyance



Yeast conveyance



Beer conveyance

# AN EXEMPLARY CONCEPT

SLH pumps feature no metal-to-metal contact between the pump screws and the housing. This enables the conveyance of non-lubricating or corrosive and contaminated materials. As the pump rotates, the intermeshing of the two screws along with the pump housing form chambers. These chambers fill with the pumped fluid and move it from the suction side of the pump to the higher pressure discharge side of the pump.



Very flexible: The pump is designed to allow for reverse flow by simply changing the shaft direction. The

suction becomes the discharge and vice versa, all without any modifications to the pump.

Bornemann SLH pumps come with a rotation speed of up to 3,600 rpm. This range makes not only process cycles as well as CIP and SIP procedures possible with

just one pump, but also increases flexibility of use with varying viscosities, temperatures, operating pressures or

other important criteria where efficient and profitable production are the objective.



# BORNEMANN PUMPS FOR FOOD AND MORE...

## BEVERAGE INDUSTRY

- Juices
- Concentrates
- Syrups
- Wines
- Sparkling wine
- Malt extract

## CONVENIENCE

- Oils & greases
- Soups
- Sauces
- Dressings
- Ketchup
- Porridge
- Dough
- Marmalade
- Mousse
- Honey
- Spreads
- Salads
- Meats
- Fish
- Delicacies
- Baby food
- Products in chunky form

## DAIRY PRODUCTS

- Yoghurt
- Quark
- Single cream
- Butter
- Cream
- Pudding
- Desserts
- Concentrates
- Melted cheese
- Curds

## SWEETS

- Chocolate
- Cream
- Fudge
- Molasses
- Liquid sugar
- Raw mixtures
- Fillings

## MEAT PRODUCTS

- Sausage meat
- Sausage prep
- Pet food

## PHARMACEUTICAL INDUSTRY

- Cosmetics
- Raw materials

...AND WHAT INDUSTRY DO YOU CALL HOME?



Beverage industry



Convenience



Dairy products



Sweets



Meat products



Pharmaceutical industry