Hanada





Yamada FDA compliant pumps are specifically designed for Food, Pharmaceutical & Cosmetic industries where 3A or EHEDG + USDA standards are not required. Pumps include 316 Stainless Steel wetted components with Passivated satin finish, Epoxy coated air motor, Sanitary clamp fittings, and FDA compliant elastomers: Hytrel®, EPDM and PTFE.

☐ FEATURES

- 316 stainless steel housings passivated satin finish
- FDA compliant elastomers
- Sanitary clamp fittings
- Epoxy coated air motor
- Handles a wide variety of fluids with high solids content
- Self priming
- Ability to run dry without damage
- Portable
- No mechanical seals, couplings or motors
- Variable flow rate



Yamada FDA Compliant pumps

□ SPECIFICATIONS

Pump model	Size	Diaphragm	Net weight	Liquid temp °C	Solid size
NDP-5FST-FDA	3/4"	PTFE	3,0 Kg	100	0,0 mm
DP-10BSH-FDA	3/4"	Hytrel®	6,5 Kg	120	1,0 mm
DP-10BST-FDA	3/4"	PTFE	6,5 Kg	100	1,0 mm
NDP-15BSH-FDA	1"	Hytrel®	6,6 Kg	120	1,0 mm
NDP-15BST-FDA	1"	PTFE	6,6 Kg	100	1,0 mm
NDP-20BSH-FDA	1"	Hytrel®	15,0 Kg	120	2,0 mm
NDP-20BSE-FDA	1"	EPDM	15,0 Kg	82	2,0 mm
NDP-20BST-FDA	1"	PTFE	15,0 Kg	100	2,0 mm
NDP-25BSH-FDA	1-1/2"	Hytrel®	23,0 Kg	120	4,8 mm
NDP-25BSE-FDA	1-1/2"	EPDM	23,0 Kg	82	4,8 mm
NDP-25BST-FDA	1-1/2"	PTFE	23,0 Kg	100	4,8 mm
NDP-40BSH-FDA	2"	Hytrel®	52,0 Kg	120	7,0 mm
NDP-40BSE-FDA	2"	EPDM	52,0 Kg	82	7,0 mm
NDP-40BST-FDA	2"	PTFE	52,0 Kg	100	7,0 mm
NDP-50BSH-FDA	2-1/2"	Hytrel®	60,0 Kg	120	8,0 mm
NDP-50BSE-FDA	2-1/2"	EPDM	60,0 Kg	82	8,0 mm
NDP-50BST-FDA	2-1/2"	PTFE	60,0 Kg	100	8,0 mm
NDP-80BSH-FDA	4"	Hytrel®	111,5 Kg	120	10,0 mm
NDP-80BSE-FDA	4"	EPDM	111,5 Kg	82	10,0 mm
NDP-80BST-FDA	4"	PTFE	111,5 Kg	100	10,0 mm





NDP-20BST-FDA-D

Yamada Europe B.V.

Aquamarijnstraat 50 7554 NS Hengelo The Netherlands

Phone : +31 (0)74-24 220 32 Fax : +31 (0)74-24 210 55

Email: sales@yamada-europe.com





Yamada Distributor